

View Online at <https://aerobasegroup.com/nsn/5935-00-082-1388>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Angle shape, external/internal coupling

Overall Length:

2.125 inches

Overall Height:

1.500 inches

Overall Width:

0.813 inches

Environmental Protection:

Shock proof and vibration proof and cold resistant and heat resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

N all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Frequency Rating:

11000.0 megahertz all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thread Length:

0.187 inches

Thread Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Contact Surface Treatment:

Gold all mating ends single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 type 2, cl 2 military specification single treatment response all mating ends single contact grouping

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial pin all mating ends single contact grouping

Special Features:

Adapter is u shaped

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.