NSN 5935-00-082-1432

Between 1.490 inches and 1.510 inches

Between 0.516 inches and 0.547 inches

Between 0.333 inches and 0.353 inches

Between 1.245 inches and 1.255 inches

Distance Between Mounting Facility Centers:

Thread Class:

Right-hand

Body Style:

Straight shape

Overall Length:

Thread Direction:

Overall Height:

Overall Width:

Threaded Device Type:

2a

Electrical Receptacle Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-082-1432

Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 26 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 400.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Included Contact Quantity:** 26 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping

NSN 5935-00-082-1432

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.026 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0