NSN 5935-00-085-0330

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-085-0330

Body	Style:
------	--------

Straight edge type w/mounting flange

Overall Length:

4.360 inches

Overall Height:

0.660 inches

Overall Width:

0.350 inches

Environmental Protection:

Heat resistant and cold resistant and vibration resistant and shock resistant and moisture resistant

Unthreaded Mounting Hole Diameter:

0.180 inches

Distance Between Mounting Facility Centers:

4.055 inches

Board Accommodated Length:

3.596 inches single board

Board Accommodated Width:

0.074 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

800.0 single mating end single contact grouping

Polarization Method:

Fixed contact to contact

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

NSN 5935-00-085-0330

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Insert Material Specification:
Mil-m-14, type sdg military specification single material response single mating end
Included Contact Quantity:
22 single mating end single contact grouping
Included Contact Type:
Leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.022 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Demilitarization: