## NSN 5935-00-086-8922

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-086-8922

**Body Style:** 

Wall type w/ or w/o cover

**Overall Length:** 

4.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches

**Overall Height:** 

3.375 inches

**Unthreaded Mounting Hole Diameter:** 

0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

3.062 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

"3, 5-50, 6-50" single mating end

**Contact Removability:** 

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:** 

15.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:** 

125.0 single mating end all contact groupings

**Polarization Method:** 

Contact

Shell Type:

Split

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Nickel single mating end all contact groupings

**Insert Material:** 

Plastic phenolic single mating end

**Contact Surface Treatment Specification:** 

Qq-n-290 cl 2, type 6 federal specification single treatment response single mating end all contact groupings

**Terminal Type:** 

Screw single mating end all contact groupings

**Shell Material:** 

Aluminum alloy

# NSN 5935-00-086-8922

Electrical Receptacle Connector - Page 2 of 2



#### **Insert Material Specification:**

Mil-m-14 ty cfi-5 military specification single material response single mating end

### **Included Contact Quantity:**

2 single mating end 2nd contact grouping

### **Included Contact Type:**

U-socket single mating end 1st contact grouping

### **Test Data Document:**

81349-mil-r-2726 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-r-2726/37 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.