

View Online at <https://aerobasegroup.com/nsn/5935-00-086-8923>

Body Style:

Wall type

Overall Height:

1.203 inches

Overall Width:

1.406 inches

Environmental Protection:

Watertight

Unthreaded Mounting Hole Diameter:

0.164 inches

Distance Between Mounting Facility Centers:

1.937 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

"3, 5-50, 6-50" single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

15.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end all contact groupings

Polarization Method:

Contact

Connector Locking Method:

Friction

Terminal Location:

Side single mating end 2nd contact grouping

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Nickel single mating end all contact groupings

Insert Material:

Plastic phenolic single mating end

Contact Surface Treatment Specification:

Qq-n-290, class 2, type 6 federal specification single treatment response single mating end all contact groupings

Terminal Type:

Screw single mating end all contact groupings

Insert Material Specification:

Mil-m-14, type cfi-5 military specification single material response single mating end

Included Contact Quantity:

2 single mating end 2nd contact grouping

Included Contact Type:

Flat socket single mating end 2nd contact grouping

Test Data Document:

81349-mil-r-2726 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-2726/37 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.