

View Online at <https://aerobasegroup.com/nsn/5935-00-086-9145>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

Between 1.932 inches and 1.946 inches

Overall Height:

Between 1.368 inches and 1.382 inches

Overall Width:

Between 1.368 inches and 1.382 inches

Environmental Protection:

Fungus resistant and moisture resistant and pressure proof

Unthreaded Mounting Hole Diameter:

Between 0.013 inches and 0.027 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.055 inches and 1.069 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.055 inches and 1.069 inches

Distance From Mounting Shoulder To Front Face:

Between 0.743 inches and 0.757 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

15.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

18

Thread Size:

1.125 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic melamine single mating end

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Insert Material Specification:

Mil-m-14, type mme military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.001 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.