

View Online at <https://aerobasegroup.com/nsn/5935-00-087-5762>

Body Style:

Straight shape

Overall Length:

1.198 inches

Overall Diameter:

Between 0.540 inches and 0.580 inches

Environmental Protection:

Vibration proof

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Tps all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends all contact groupings

Contact Maximum Frequency Rating:

10000.0 megahertz all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and silver all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene all mating ends

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

2 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial pin all mating ends all contact groupings

Precious Material And Location:

Contact surfaces gold and contact and shell surfaces silver

Precious Material And Weight:

0.010 gold grains, troy and 0.110 silver grains, troy

Precious Material:

Gold and silver

Reference Number Differentiating Characteristics:

As differentiated by nothing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0