## NSN 5935-00-087-8552

Electrical Receptacle Connector - Page 1 of 2



Body Style:
Straight shape, external coupling
Overall Length:
1.067 inches
Overall Height:
1.312 inches
Overall Width:
1.312 inches
Unthreaded Mounting Hole Diameter:
Between 0.120 inches and 0.130 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.062 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.062 inches
Distance From Mounting Shoulder To Front Face:
0.562 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
18-24 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
45.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:

Terminal Type

Solder well single mating end single contact grouping

## NSN 5935-00-087-8552

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Included Contact Quantity:
24 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.024 gold grains, troy and 0.024 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0