NSN 5935-00-087-9832

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-087-9832

Body Style: Straight shape, external coupling w/backshell **Overall Length:** 1.125 inches **Overall Height:** 1.438 inches **Overall Width:** 1.438 inches **Environmental Protection:** Corrosion resistant and humidity resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.187 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.187 inches **Distance From Mounting Shoulder To Front Face:** 0.531 inches **Mating End Quantity: Contact Position Arrangement Style:** 3719p single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 7.5 single mating end 2nd contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end all contact groupings **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 50.0 Shell Type: Solid **Connector Locking Method:**

Bayonet pin

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

NSN 5935-00-087-9832

Electrical Receptacle Connector - Page 2 of 2



Insert Material:	
Plastic single mating end	
Contact Surface Treatment Specification:	
Mil-g-14548, type 1, cl 1 military specification 1st treatment response single mating end all contact groupings and qualitary	q-s-365 federal
specification 2nd treatment response single mating end all contact groupings	
Terminal Type:	
Solder well single mating end all contact groupings	
Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Anodize	
Included Contact Quantity:	
6 single mating end 1st contact grouping	
Included Contact Type:	
Round pin single mating end 2nd contact grouping	
Precious Material And Location:	
Contact surfaces gold and contact surfaces silver	
Precious Material And Weight:	
0.048 gold grains, troy and 0.048 silver grains, troy	
Precious Material:	
Gold and silver	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: A039b0

Mil-std (military Standard):

Mil-g-14548 spec.