## NSN 5935-00-088-1129

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-088-1129

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

5.359 inches

**Overall Height:** 

0.656 inches

**Overall Width:** 

0.428 inches

**Unthreaded Mounting Hole Diameter:** 

0.125 inches

**Distance Between Mounting Facility Centers:** 

Between 5.102 inches and 5.116 inches

**Board Accommodated Length:** 

4.651 inches single board and 4.661 inches single board

**Board Accommodated Width:** 

0.062 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

Bridged contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

10.0 single mating end single contact grouping

**Polarization Method:** 

Fixed contact to contact

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

**Insert Material Specification:** 

Mil-; -19833, type gdi-30 military specification single material response single mating end

**Included Contact Quantity:** 

28 single mating end single contact grouping

**Included Contact Type:** 

Leaf spring single mating end single contact grouping

## NSN 5935-00-088-1129

Electrical Receptacle Connector - Page 2 of 2



## Special Features: Polarizing key in contact pos s Precious Material And Location: Contact surfaces gold and contact surfaces silver Precious Material And Weight: 0.028 gold grains, troy and 0.028 silver grains, troy Precious Material: Gold and silver Shelf Life: N/a Unit Of Measure: -Demilitarization: No Fiig: A039b0

Mil-std (military Standard):

spec.