

View Online at <https://aerobasegroup.com/nsn/5935-00-088-2319>

Thread Class:

2a

Thread Direction:

Right-hand

Body Length:

0.900 inches

Overall Diameter:

0.720 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Latching ring

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Astmb30159 assn standard single material response single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-n-26074 military specification single treatment response

Shell Material Specification:

Qq-a-268, t4 federal specification single material response

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

Included Contact Quantity:

7 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.007 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.