NSN 5935-00-088-2690

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-088-2690 **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 0.910 inches **Overall Height:** 1.328 inches **Overall Width:** 1.328 inches **Environmental Protection:** Moisture proof **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.057 inches and 1.067 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.057 inches and 1.067 inches **Distance From Mounting Shoulder To Front Face:** Between 0.452 inches and 0.462 inches **Mating End Quantity: Contact Position Arrangement Style:** 16-55 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

NSN 5935-00-088-2690

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:	
Crimp single mating end single contact grouping	
Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Cadmium and chromate	
Insert Material Specification:	
Mil-m-14, type sdg-f military specification single material response single mating end	
Included Contact Quantity:	
55 single mating end single contact grouping	
Included Contact Type:	
Round socket single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.055 gold grains, troy	
Precious Material:	
Gold	
Test Data Document:	
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data	in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data	on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Specification Data:	
81349-mil-c-26482 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-m-14 spec.	