## NSN 5935-00-088-3157

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-088-3157 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.406 inches **Overall Diameter:** 1.125 inches **Environmental Protection:** Salt water resistant and vibration resistant **Distance From Mounting Shoulder To Front Face:** 0.625 inches **Mounting Facility Thickness:** 0.141 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 14s-2 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell **Thread Length:** 

0.450 inches

Thready Qty Per Inch (tpi):

20 and 20

## NSN 5935-00-088-3157

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
0.875 inches and 0.750 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Steel single mating end single contact grouping
Contact Surface Treatment:
Tin single mating end single contact grouping and cadmium single mating end single contact grouping
Insert Material:
Glass single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Tin and cadmium
Included Contact Quantity:
4 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Hermetically sealed
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0