Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-088-5106

Body Style:

Straight shape, external coupling strain relief

Overall Height:

Between 1.546 inches and 1.578 inches

Overall Width:

Between 1.546 inches and 1.578 inches

Body Length:

2.266 inches

Environmental Protection:

Moisture proof

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Cable Entrance Diameter:

0.750 inches

Distance From Mounting Shoulder To Front Face:

Between 0.556 inches and 0.566 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

22-21 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

349.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cable clamp

NSN 5935-00-088-5106

Electrical Receptacle Connector - Page 2 of 2



Terminal Location: Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Rubber natural single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 21 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.210 gold grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0