## NSN 5935-00-088-8230

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-088-8230
Body Style:
Straight shape, external coupling
Overall Length:
0.835 inches
Overall Height:
1.125 inches
Overall Width:
1.125 inches
Environmental Protection:
Moisture resistant
Unthreaded Mounting Hole Diameter:
0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.906 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.906 inches
Distance From Mounting Shoulder To Front Face:
0.562 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
14-12 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Terminal Location:
Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

## NSN 5935-00-088-8230

Electrical Receptacle Connector - Page 2 of 2



## **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize **Insert Material Specification:** Mil-m-14 military specification single material response single mating end **Included Contact Quantity:** 12 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surface gold and contact surface silver **Precious Material And Weight:** 0.012 gold grains, troy and 0.012 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.