NSN 5935-00-088-8650

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-088-8650
Body Style:
Straight shape, flange mount, external coupling
Overall Length:
1.734 inches
Overall Height:
1.437 inches
Overall Width:
1.437 inches
Environmental Protection:
Heat resistant and moisture resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.156 inches
Distance From Mounting Shoulder To Front Face:
0.562 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
20-66 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
17.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
225.0
Shell Type:
Potting

Potting

Connector Locking Method:

Bayonet slot

Connector Cable Strain Relief Method:

Potting type

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

NSN 5935-00-088-8650

Electrical Receptacle Connector - Page 2 of 2



insert Material:	
Plastic diallyl phthalate single mating end	
Terminal Type:	
Solder well single mating end single contact grouping	
Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Anodize	
Shell Surface Treatment Specification:	
Mil-a-8625 military specification single treatment response	
Insert Material Specification:	
Mil-m-14 military specification single material response single mating end	
Included Contact Quantity:	
19 single mating end single contact grouping	
Included Contact Type:	
Round socket single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold and contact surfaces silver	
Precious Material And Weight:	
0.019 gold grains, troy and 0.019 silver grains, troy	
Precious Material:	
Gold and silver	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-m-14 spec.	