# NSN 5935-00-088-8650

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-088-8650

### Body Style:

Straight shape, flange mount, external coupling

### **Overall Length:**

1.734 inches

# **Overall Height:**

1.437 inches

### **Overall Width:**

1.437 inches

#### **Environmental Protection:**

Heat resistant and moisture resistant and vibration resistant

#### **Unthreaded Mounting Hole Diameter:**

#### 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

#### 1.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

#### Distance De

1.156 inches

# Distance From Mounting Shoulder To Front Face:

0.562 inches

# Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

20-66 single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

17.0 single mating end single contact grouping

#### Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

225.0

#### Shell Type:

Potting

#### **Connector Locking Method:**

Bayonet slot

#### **Connector Cable Strain Relief Method:**

Potting type

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



**Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize **Shell Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Insert Material Specification:** Mil-m-14 military specification single material response single mating end **Included Contact Quantity:** 19 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.019 gold grains, troy and 0.019 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-m-14 spec.