

View Online at <https://aerobasegroup.com/nsn/5935-00-089-0609>

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.526 inches

**Overall Diameter:**

0.859 inches

**Environmental Protection:**

Moisture resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

10-98 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Potting

**Connector Locking Method:**

Bayonet latch

**Connector Cable Strain Relief Method:**

Potting type

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Chromate and cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2 federal specification single treatment response

**Included Contact Quantity:**

6 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.006 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.