## NSN 5935-00-089-2324

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-089-2324

**Body Style:** 

Straight shape

**Overall Length:** 

Between 2.620 inches and 2.650 inches

**Overall Height:** 

Between 0.419 inches and 0.439 inches

**Overall Width:** 

Between 0.479 inches and 0.509 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.086 inches and 0.091 inches

**Distance Between Mounting Facility Centers:** 

Between 2.401 inches and 2.411 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

36w4 single mating end

**Contact Removability:** 

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Gold single mating end all contact groupings and silver single mating end all contact groupings

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Solder well single mating end all contact groupings

**Shell Material:** 

Steel

**Shell Surface Treatment:** 

Cadmium and chromate

**Insert Material Specification:** 

Mil-m-14, ty sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

4 single mating end 1st contact grouping

## NSN 5935-00-089-2324

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.052 gold grains, troy and 0.052 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.