NSN 5935-00-089-2689

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-089-2689

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.500 inches
Overall Height:
1.250 inches
Overall Width:
1.250 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.875 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.875 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
12000.0 single mating end single contact grouping
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
20 and 20
Thread Size:
0.500 inches and 0.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

NSN 5935-00-089-2689

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Ceramic single mating end
Terminal Type:
Tapered pin single mating end single contact grouping
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface silver
Precious Material And Weight:
0.001 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unf and unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0