NSN 5935-00-089-6510

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-089-6510 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.531 inches **Overall Height:** 2.000 inches **Overall Width:** 2.000 inches **Environmental Protection:** Watertight **Unthreaded Mounting Hole Diameter:** Between 0.145 inches and 0.151 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.557 inches and 1.567 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.557 inches and 1.567 inches **Distance From Mounting Shoulder To Front Face:** Between 0.812 inches and 0.822 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 28-21 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:**

Externally threaded shell

Thread Length:

0.625 inches

NSN 5935-00-089-6510

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi):
18
Thread Size:
1.750 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.037 gold grains, troy and 0.037 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0