Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-090-7025

Thread Class:
2a Three d Direction
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
1.485 inches
Overall Height:
0.490 inches
Overall Width:
0.308 inches
Environmental Protection:
Moisture resistant and shock resistant and vibration proof
Unthreaded Mounting Hole Diameter:
0.091 inches
Distance Between Mounting Facility Centers:
1.265 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Contact Position Arrangement Style: 37 single mating end
37 single mating end
37 single mating end Contact Removability:
37 single mating end Contact Removability: Removable single mating end single contact grouping
37 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps:
 37 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping
 37 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method:
 37 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Jackscrew
 37 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type:
37 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid
 37 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Connector Locking Method:
37 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew
37 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew Thready Qty Per Inch (tpi):
37 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew Thready Qty Per Inch (tpi): 56
37 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew Thready Qty Per Inch (tpi): 56 Thread Size:
37 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew Thready Qty Per Inch (tpi): 56 Thread Size: 0.086 inches
37 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew Thready Qty Per Inch (tpi): 56 Thread Size: 0.086 inches Terminal Location:
37 single mating endContact Removability:Removable single mating end single contact groupingContact Maximum Current Rating In Amps:3.0 single mating end single contact groupingPolarization Method:JackscrewShell Type:SolidConnector Locking Method:JackscrewThready Qty Per Inch (tpi):56Thread Size:0.086 inchesTerminal Location:Back single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate or plastic polyester single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Insert Material Specification:

Mil-m-14 ty sdgf military specification single material response or mil-m-24519 military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

37 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Jackscrew type-male and location-left handandjackscrew type-male and location-right hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.037 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.