Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-090-7102

Body Style:
Straight shape
Overall Length:
3.969 inches
Overall Height:
0.985 inches
Overall Width:
1.250 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Mounting Facility Centers:
3.625 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
32 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Latch
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping
Contact Material Specification:
Qq-c-576 federal specification single material response single mating end single contact grouping
Shell Material:

Copper alloy

NSN 5935-00-090-7102

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Nickel Shell Surface Treatment Specification: Qq-n-290, class 2 federal specification single treatment response **Included Contact Quantity:** 32 single mating end single contact grouping Included Contact Type: Leaf spring single mating end single contact grouping **Special Features:** Polarized at positions a, d, 4 and 7 **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.032 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.