NSN 5935-00-090-7268

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-090-7268

Thread Direction: Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.111 inches **Overall Height:** Between 0.932 inches and 0.942 inches **Overall Width:** Between 0.932 inches and 0.942 inches **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.714 inches and 0.724 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.714 inches and 0.724 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 5 number 20 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Shell Surface Treatment:** Tin

Included Contact Quantity:

5 single mating end single contact grouping

NSN 5935-00-090-7268

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0