## NSN 5935-00-090-7354

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-090-7354

**Body Style:** Right angle type **Overall Length:** 2.490 inches **Overall Height:** 0.519 inches **Overall Width:** 0.301 inches **Environmental Protection:** Shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.070 inches **Distance Between Mounting Facility Centers:** 2.350 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.00 single mating end single contact grouping **Polarization Method:** Contact **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Criticality Code Justification:** Feat **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-b-750, comp a federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

41 single mating end single contact grouping

## NSN 5935-00-090-7354

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Type:** Hermaphrodite single mating end single contact grouping **Special Features:** Pin no. 29 removed **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.041 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A039b0

Mil-std (military Standard):

Mil-m-14 spec.