Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-101-5570

| Thread Class: |
|--|
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape |
| Overall Length: |
| 1.322 inches |
| Overall Height: |
| 0.780 inches |
| Overall Width: |
| Between 0.488 inches and 0.508 inches |
| Environmental Protection: |
| Humidity resistant and shock resistant and thermal shock resistant and vibration resistant |
| Distance Between Mounting Facility Centers: |
| Between 1.088 inches and 1.098 inches |
| Threaded Device Type: |
| Mounting hole |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 9 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 7.5 single mating end single contact grouping |
| Polarization Method: |
| Mating end |
| Shell Type: |
| Solid |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.112 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Contact Surface Treatment Specification: |
| |

Mil-g-45204, type 1, grade c military specification single treatment response single mating end single contact grouping



| Terminal Type | gle mating end single contact grouping |
|---|---|
| Shell Material: | |
| Aluminum alloy | |
| Shell Surface | |
| Cadmium | |
| e d d d d d d d d d d d d d d d d d d d | Treatment Specification: |
| | e 2, cl 1 federal specification single treatment response |
| | Specification: |
| | g-f military specification single material response single mating end |
| Included Cont | |
| | end single contact grouping |
| Included Cont | |
| | single mating end single contact grouping |
| | erial And Location: |
| Contact surface | |
| | erial And Weight: |
| 0.009 gold grain | |
| Precious Mate | · |
| Gold | |
| Thread Series | Designator: |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Measu | re: |
| | |
| Demilitarizatio | on: |
| No | |
| Fiig: | |
| A039b0 | |
| Mil-std (militar | ry Standard): |
| Mil-g-45204 sp | |