NSN 5935-00-102-5903

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-102-5903

| Thread Class: |
|---|
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Angle shape w/cable clamp |
| Overall Diameter: |
| 2.718 inches |
| Body Angle In Deg: |
| 135.0 |
| Cable Entrance Diameter: |
| Between 1.180 inches and 1.625 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 40-1 single mating end |
| Contact Removability: |
| Removable single mating end all contact groupings |
| Contact Maximum Current Rating In Amps: |
| 23.0 single mating end 1st contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 900.0 single mating end all contact groupings |
| Contact Maximum Dc Voltage Rating In Volts: |
| 1250.0 single mating end all contact groupings |
| Polarization Method: |
| Key, multiple key groove |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Internally threaded coupling ring |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Distance From Centerline To Connector End: |
| Between 2.781 inches and 2.843 inches |
| Distance From Centerline To Cable End: |
| 3.325 inches |
| Features Provided: |
| Safety wire hole |
| |

NSN 5935-00-102-5903Electrical Plug Connector - Page 2 of 2



| Thready Qty Per Inch (tpi): | |
|---|--|
| 16 | |
| Thread Size: | |
| 2.500 inches | |
| Terminal Location: | |
| Back single mating end all contact groupings | |
| Contact Material: | |
| Copper alloy single mating end all contact groupings | |
| Contact Surface Treatment: | |
| Gold single mating end all contact groupings and silver single mating end all contact groupings | |
| Insert Material: | |
| Rubber single mating end | |
| Crimping Tool Identifying Number: | |
| 77820-11-7295 | |
| Terminal Type: | |
| Crimp single mating end all contact groupings | |
| Shell Material: | |
| Aluminum alloy | |
| Shell Surface Treatment: | |
| Cadmium and chromate | |
| Included Contact Quantity: | |
| 6 single mating end 1st contact grouping | |
| Included Contact Type: | |
| Round socket single mating end all contact groupings | |
| Precious Material And Location: | |
| Contact surfaces gold and contact surfaces silver | |
| Precious Material And Weight: | |
| 0.030 gold grains, troy and 0.030 silver grains, troy | |
| Precious Material: | |
| Gold and silver | |
| Thread Series Designator: | |
| Un | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A039b0 | |
| | |