NSN 5935-00-102-6031

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-102-6031

Thread Class: 2b Thread Direction: Right-hand Body Style: Angle, shape, internal coupling Overall Length: 1.190 inches Overall Height: 2.250 inches Overall Diameter: 0.687 inches Body Angle In Deg: 90.0 Environmental Protection: Salt water resistant Cable Entrance Diameter: 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity: 1
Thread Direction: Right-hand Body Style: Angle, shape, internal coupling Overall Length: 1.190 inches Overall Height: 2.250 inches Overall Diameter: 0.687 inches Body Angle In Deg: 90.0 Environmental Protection: Salt water resistant Cable Entrance Diameter: 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity:
Right-hand Body Style: Angle, shape, internal coupling Overall Length: 1.190 inches Overall Height: 2.250 inches Overall Diameter: 0.687 inches Body Angle In Deg: 90.0 Environmental Protection: Salt water resistant Cable Entrance Diameter: 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity:
Body Style: Angle, shape, internal coupling Overall Length: 1.190 inches Overall Height: 2.250 inches Overall Diameter: 0.687 inches Body Angle In Deg: 90.0 Environmental Protection: Salt water resistant Cable Entrance Diameter: 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity:
Angle, shape, internal coupling Overall Length: 1.190 inches Overall Height: 2.250 inches Overall Diameter: 0.687 inches Body Angle In Deg: 90.0 Environmental Protection: Salt water resistant Cable Entrance Diameter: 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity:
Overall Length: 1.190 inches Overall Height: 2.250 inches Overall Diameter: 0.687 inches Body Angle In Deg: 90.0 Environmental Protection: Salt water resistant Cable Entrance Diameter: 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity:
1.190 inches Overall Height: 2.250 inches Overall Diameter: 0.687 inches Body Angle In Deg: 90.0 Environmental Protection: Salt water resistant Cable Entrance Diameter: 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity:
Overall Height: 2.250 inches Overall Diameter: 0.687 inches Body Angle In Deg: 90.0 Environmental Protection: Salt water resistant Cable Entrance Diameter: 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity:
2.250 inches Overall Diameter: 0.687 inches Body Angle In Deg: 90.0 Environmental Protection: Salt water resistant Cable Entrance Diameter: 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity:
Overall Diameter: 0.687 inches Body Angle In Deg: 90.0 Environmental Protection: Salt water resistant Cable Entrance Diameter: 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity:
0.687 inches Body Angle In Deg: 90.0 Environmental Protection: Salt water resistant Cable Entrance Diameter: 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity:
Body Angle In Deg: 90.0 Environmental Protection: Salt water resistant Cable Entrance Diameter: 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity:
90.0 Environmental Protection: Salt water resistant Cable Entrance Diameter: 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity:
Environmental Protection: Salt water resistant Cable Entrance Diameter: 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity:
Salt water resistant Cable Entrance Diameter: 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity:
Cable Entrance Diameter: 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity:
0.438 inches Threaded Device Type: Coupling facility Mating End Quantity:
Threaded Device Type: Coupling facility Mating End Quantity:
Coupling facility Mating End Quantity:
Mating End Quantity:
1
Contact Position Arrangement Style:
Hn single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1500.0 single mating end single contact grouping
Contact Maximum Frequency Rating:
10000.0 megahertz single mating end single contact grouping
Polarization Method:
Contact
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Connector Cable Strain Relief Method:
Compression nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping

Thread Size: 0.750 inches

NSN 5935-00-102-6031Electrical Plug Connector - Page 2 of 2

A039b0



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-c-530, comp ht federal specification single material response single mating end single contact grouping
Shell Material:
Copper alloy
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: