
## NSN 5935-00-102-7999

Tip Jack - Page 1 of 2

**Thread Class:** 





2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated from panel **Identification Code Color:** Purple **Body Style:** Threaded bushing mounted **Overall Length:** 1.000 inches Mounting Bushing Length: 0.438 inches **Body Length:** 0.617 inches **Overall Diameter:** 0.281 inches **Bushing Accommodation Hole Shape:** Round Maximum Voltage Rating In Volts: 3000.0 ac Accommodated Finger Type: Test prod single finger **Finger Accommodation Diameter:** 0.080 inches single finger Finger Accommodation Length: 0.500 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.250 inches **Current Rating In Amps:** 5.0 Mounting Facility Type And Quantity: 1 bushing **Thread Size:** 0.250 inches **Terminal Type:** Turret Material: Copper terminal Material: Copper terminal

NSN 5935-00-102-7999

Tip Jack - Page 2 of 2



Precious Material And Location:

Spring contact surface gold

Precious Material:

Gold

Surface Treatment:

Gold spring

Surface Treatment:

Gold spring

## **Test Data Document:**

81349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef

## **Specification Data:**

81349-mil-c-39024/10 government specification

Shelf Life:

N/a

---

Unit Of Measure:

Demilitarization:

No

Fiig:

A03400