## NSN 5935-00-102-7999

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-102-7999 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated from panel **Identification Code Color:** Purple **Body Style:** Threaded bushing mounted **Overall Length:** 1.000 inches **Mounting Bushing Length:** 0.438 inches **Body Length:** 0.617 inches **Overall Diameter:** 0.281 inches **Bushing Accommodation Hole Shape:** Round **Maximum Voltage Rating In Volts:** 3000.0 ac **Accommodated Finger Type:** Test prod single finger **Finger Accommodation Diameter:** 0.080 inches single finger **Finger Accommodation Length:** 0.500 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.250 inches **Current Rating In Amps: Mounting Facility Type And Quantity:** 1 bushing **Thread Size:** 0.250 inches **Terminal Type:** Turret Material: Copper terminal

Copper terminal

Material:

Copper terminal

## **NSN 5935-00-102-7999** Tip Jack - Page 2 of 2



Precious Material And Location:
Spring contact surface gold
Precious Material:
Gold
Surface Treatment:
Gold spring
Surface Treatment:
Gold spring
Test Data Document:
31349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Jnef
Specification Data:
31349-mil-c-39024/10 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A03400