NSN 5935-00-102-8279

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-102-8279

Body Style:

Straight edge type w/mounting flange

Overall Length:

2.990 inches

Overall Height:

0.312 inches

Overall Width:

0.245 inches

Environmental Protection:

Dripproof and salt water resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.078 inches

Distance Between Mounting Facility Centers:

2.850 inches

Board Accommodated Length:

2.550 inches single board

Board Accommodated Width:

0.100 inches

Mating End Quantity:

VIC

Contact Position Arrangement Style:

Bridged contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Fixed contact to contact

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

NSN 5935-00-102-8279

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 52 single mating end single contact grouping **Included Contact Type:** Hermaphrodite single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.052 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):