Steel

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-102-9552

| View Online at https://aerobasegroup.com/nsi//3933-00-102-9332 |
|---|
| Body Style: |
| Straight shape |
| Overall Length: |
| 2.729 inches |
| Overall Height: |
| 0.494 inches |
| Overall Width: |
| 0.546 inches |
| Environmental Protection: |
| Weather resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.120 inches |
| Distance Between Mounting Facility Centers: |
| 2.500 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 79 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Polarization Method: |
| Mating end |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Friction |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |

Electrical Receptacle Connector - Page 2 of 2

