

View Online at <https://aerobasegroup.com/nsn/5935-00-103-3946>

**Thread Class:**

2b and 2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling w/backshell

**Overall Length:**

1.938 inches

**Overall Diameter:**

1.588 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

22-19 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

13.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling ring

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.375 inches and 1.187 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification 1st treatment response

**Insert Material Specification:**

Mil-r-3065 military specification single material response single mating end

**Included Contact Quantity:**

14 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Contact arrangement 22-68

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.014 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-r-3065 spec.