NSN 5935-00-103-4172

Tip Jack - Page 1 of 2

Electrical Insulation Feature:

Identification Code Color:

Insulated completely

Blue

Body Style:



View Online at https://aerobasegroup.com/nsn/5935-00-103-4172

Press fit
Overall Length:
0.637 inches
Body Length:
0.450 inches
Overall Diameter:
0.218 inches
Bushing Accommodation Hole Shape:
Round
Maximum Voltage Rating In Volts:
1000.0 ac
Accommodated Finger Type:
Test prod single finger
Finger Accommodation Diameter:
0.080 inches single finger
Finger Accommodation Length:
0.312 inches single finger
Bushing Thru-hole Accommodation Diameter:
0.185 inches
Capacitance In Picofarads:
•
0.7
•
0.7
0.7 Current Rating In Amps:
0.7 Current Rating In Amps: 5.5
0.7 Current Rating In Amps: 5.5 Mounting Facility Type And Quantity:
0.7 Current Rating In Amps: 5.5 Mounting Facility Type And Quantity: 1 bushing
0.7 Current Rating In Amps: 5.5 Mounting Facility Type And Quantity: 1 bushing Terminal Type:
0.7 Current Rating In Amps: 5.5 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug
0.7 Current Rating In Amps: 5.5 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material:
0.7 Current Rating In Amps: 5.5 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
0.7 Current Rating In Amps: 5.5 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body Material:
0.7 Current Rating In Amps: 5.5 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body Material: Plastic polytetrafluoroethylene insulator
Current Rating In Amps: 5.5 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body Material: Plastic polytetrafluoroethylene insulator Precious Material And Location:
Current Rating In Amps: 5.5 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body Material: Plastic polytetrafluoroethylene insulator Precious Material And Location: Spring contact surfaces gold and spring contact surface silver
Current Rating In Amps: 5.5 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body Material: Plastic polytetrafluoroethylene insulator Precious Material And Location: Spring contact surfaces gold and spring contact surface silver Precious Material And Weight:
Current Rating In Amps: 5.5 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body Material: Plastic polytetrafluoroethylene insulator Precious Material And Location: Spring contact surfaces gold and spring contact surface silver Precious Material And Weight: 0.005 gold grains, troy and 0.005 silver grains, troy

NSN 5935-00-103-4172

Tip Jack - Page 2 of 2



_		_			
S	rface	\ Irc	natre	าดท	

Gold and silver spring

Surface Treatment:

Gold spring and silver spring

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A03400