NSN 5935-00-103-4178



| Tip Jack - Page 1 of 2 | Group |
|---|-------|
| View Online at https://aerobasegroup.com/nsn/5935-00-103-4178 | |
| Electrical Insulation Feature: | |
| Insulated completely | |
| Identification Code Color: | |
| Violet | |
| Body Style: | |
| Press fit | |
| Overall Length: | |
| 0.637 inches | |
| Body Length: | |
| 0.450 inches | |
| Overall Diameter: | |
| 0.218 inches | |
| Bushing Accommodation Hole Shape: | |
| Round | |
| Maximum Voltage Rating In Volts: | |
| 1000.0 ac | |
| Accommodated Finger Type: | |
| Test prod single finger | |
| Finger Accommodation Diameter: | |
| 0.080 inches single finger | |
| Finger Accommodation Length: | |
| 0.312 inches single finger | |
| Bushing Thru-hole Accommodation Diameter: | |
| 0.185 inches | |
| Capacitance In Picofarads: | |
| 0.7 | |
| Current Rating In Amps: | |
| 5.5 | |
| Mounting Facility Type And Quantity: | |
| 1 bushing | |
| Terminal Type: | |
| Tab, solder lug | |
| Material: | |

Material:

Plastic, polytetrafluoroethylene body

Material:

Plastic polytetrafluoroethylene insulator

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material And Weight:

0.005 gold grains, troy and 0.005 silver grains, troy

Precious Material:

Gold and silver

NSN 5935-00-103-4178

Tip Jack - Page 2 of 2



| _ | | _ | | | |
|------|-------|-----|-----|-----|----|
| C 11 | rface | Iro | 2tm | ıαn | ٠. |
| | | | | | |

Gold and silver spring

Surface Treatment:

Gold spring and silver spring

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03400