NSN 5935-00-103-7653

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-103-7653

Body Style:

Straight edge type

Overall Length:

Between 4.270 inches and 4.300 inches

Overall Height:

0.692 inches

Overall Width:

0.340 inches

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Mounting Facility Centers:

4.031 inches

Board Accommodated Length:

3.596 inches single board

Board Accommodated Width:

0.062 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

830.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1270.0 single mating end single contact grouping

Polarization Method:

Inter-contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Included Contact Quantity:

44 single mating end single contact grouping

NSN 5935-00-103-7653

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Type:
----------	---------	-------

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.044 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0