

View Online at <https://aerobasegroup.com/nsn/5935-00-104-1306>

**Thread Class:**

2b and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape threaded

**Overall Length:**

0.890 inches

**Overall Diameter:**

1.750 inches

**Environmental Protection:**

Pressure proof

**Distance From Mounting Shoulder To Front Face:**

0.775 inches

**Threaded Device Type:**

Coupling facility and mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

4-55 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1200.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thread Size:**

1.500 inches and 1.625 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold and nickel single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Included Contact Quantity:**

55 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.055 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**FiiG:**

A039b0