

NSN 5935-00-104-1412

Electrical Neceptacle Confidencial - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5935-00-104-1412	
Thread Class:	
2a	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape	
Overall Length:	
2.100 inches	
Overall Width:	
0.360 inches	
Distance Between Mounting Facility Centers:	
1.800 inches	
Threaded Device Type:	
Mounting stud	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
15 single mating end	
Contact Removability:	
Removable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
7.5 single mating end single contact grouping	
Polarization Method:	
Guide pin/socket	
Thready Qty Per Inch (tpi):	
40	
Thread Size:	
0.112 inches	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold and silver single mating end single contact grouping	

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Crimp single mating end single contact grouping

Insert Material Specification:

Mil-p-19833 ty gdi-30 military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

NSN 5935-00-104-1412

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

15 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.015 gold grains, troy and 0.015 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.