## NSN 5935-00-104-1448

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-104-1448

**Body Style:** Straight shape **Overall Length:** 3.125 inches **Overall Height:** 0.672 inches **Overall Width:** 0.375 inches **Distance Between Mounting Facility Centers:** 2.900 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Connector Locking Method:** Jackscrew-socket **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-b-626 federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14, ty mdg military specification single material response single mating end **Included Contact Quantity:** 50 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping

Precious Material And Location:
Contact surfaces gold and contact surfaces silver

## NSN 5935-00-104-1448

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:		
0.050 gold grains,	troy and 0.050 silver grains,	troy
Precious Material:		
Gold and silver		
Shelf Life:		
N/a		
Unit Of Measure:		
Demilitarization:		
No		
Fiig:		
A039b0		

Mil-std (military Standard):

Mil-m-14 spec.