## NSN 5935-00-104-4600

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-104-4600

View Online at https://aerobasegroup.com/nsn/5935-00-104-4600
Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
Between 1.390 inches and 1.422 inches
Overall Height:
2.000 inches
Overall Width:
Between 1.984 inches and 2.016 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration resistant
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.553 inches and 1.573 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.553 inches and 1.573 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
28-12 single mating end
28-12 single mating end  Contact Removability:
Contact Removability:
Contact Removability:  Removable single mating end single contact grouping
Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps:
Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping
Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts:
Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping
Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts:
Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 500.0 single mating end single contact grouping
Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method:
Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway
Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg:
Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 270.0
Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 270.0 Shell Type:
Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 270.0 Shell Type: Solid

## NSN 5935-00-104-4600

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
0.190 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-b-626, temper 1/2 hard federal specification single material response single mating end single contact grouping
Shell Material:
Aluminum alloy 413.0 or aluminum alloy a380.0 or aluminum alloy a413.0 or aluminum alloy 380.0
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Insert Material Specification:
Mil-m-14, ty mdg military specification single material response single mating end
Included Contact Quantity:
26 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):