

View Online at <https://aerobasegroup.com/nsn/5935-00-104-8497>

Body Style:

Straight shape, flush mount

Overall Length:

Between 1.046 inches and 1.076 inches

Overall Height:

Between 3.060 inches and 3.090 inches

Overall Width:

Between 1.985 inches and 2.015 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.783 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Distance From Mounting Shoulder To Front Face:

0.060 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

C2 1st mating end

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

5.0 2nd mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends all contact groupings

Contact Maximum Frequency Rating:

4500.0 megahertz 1st mating end all contact groupings

Polarization Method:

1 polarization post

Shell Type:

Solid

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 1st mating end all contact groupings

Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Copper alloy 2nd mating end all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and silver all mating ends all contact groupings

Insert Material:

Plastic melamine single mating end

Terminal Type:

Solder well all mating ends all contact groupings

Contact Material Specification:

Qq-b-626, comp 22 federal specification single material response 1st mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Insert Material Specification:

Mil-m-14, type mme military specification single material response single mating end

Special Features:

Polarizing key 4-4-2

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.067 gold grains, troy and 0.067 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.