

View Online at <https://aerobasegroup.com/nsn/5935-00-105-0010>

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.526 inches

**Overall Diameter:**

1.156 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

14-5 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

900.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

1250.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Potting

**Connector Locking Method:**

Bayonet latch

**Connector Cable Strain Relief Method:**

Potting type

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

5 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.