

View Online at <https://aerobasegroup.com/nsn/5935-00-105-5530>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external/internal coupling

Overall Length:

1.390 inches

Overall Diameter:

0.625 inches

Environmental Protection:

Weatherproof and shock resistant and vibration resistant and moisture resistant and corrosion resistant and pressure proof

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Tnc 2nd mating end

Contact Removability:

Removable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1500.0 all mating ends single contact grouping

Contact Maximum Frequency Rating:

11.0 gigahertz all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thread Length:

0.180 inches

Thread Qty Per Inch (tpi):

24

Thread Size:

0.624 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping and silver all mating ends single contact grouping

Insert Material:

Plastic all mating ends

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0