Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-106-2886

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
0.900 inches
Overall Diameter:
0.530 inches
Environmental Protection:
Moisture resistant and salt water resistant and shock resistant and vibration resistant
Cable Entrance Diameter:
0.260 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded coupling nut
Connector Cable Strain Relief Method:
Cable clamp
Thready Qty Per Inch (tpi):
32
Thread Size:
0.437 inches
Terminal Location:
Back single mating end single contact grouping Contact Material:
Copper alloy single mating end single contact grouping Insert Material:
Plastic polyamide single mating end

NSN 5935-00-106-2886 Electrical Plug Connector - Page 2 of 2



Terminal Type:	
Solder well single	mating end single contact grouping
Shell Material:	
Copper alloy	
Shell Surface Tre	atment:
Cadmium	
Shell Surface Tre	atment Specification:
Qq-p-416, type 2,	class 3 federal specification single treatment response
Shell Material Sp	ecification:
Qq-b-626, comp 2	2, 1/2 hard federal specification single material response or qq-b-613, comp 2, 1/2 hard federal specification single
material response	
Insert Material Sp	pecification:
Mil-m-20693, type	2 military specification single material response single mating end
Included Contact	Quantity:
2 single mating en	d single contact grouping
Included Contact	Туре:
Round pin single r	nating end single contact grouping
Thread Series De	signator:
Unef	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military S	Standard):
Mil-m-20693 spec	