

View Online at <https://aerobasegroup.com/nsn/5935-00-106-3767>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.109 inches

**Overall Diameter:**

0.562 inches

**Environmental Protection:**

Shock resistant and vibration resistant and weatherproof

**Cable Entrance Diameter:**

0.247 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Tps single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1500.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Connector Cable Strain Relief Method:**

Compression nut

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.375 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Surface Treatment:**

Silver

**Included Contact Quantity:**

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.105 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0