

View Online at <https://aerobasegroup.com/nsn/5935-00-106-6950>

Thread Class:

2a and 2b and 3a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

T-shape

Overall Height:

1.404 inches

Overall Width:

0.800 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

N all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell and internally threaded coupling nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thready Qty Per Inch (tpi):

24 and 24 and 16

Thread Size:

0.625 inches and 0.625 inches and 0.750 inches

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and nickel all mating ends all contact groupings

Insert Material:

Plastic all mating ends

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Surface Treatment Specification:

Qq-s-365 federal specification single treatment response

Included Contact Quantity:

1 2nd mating end all contact groupings

Included Contact Type:

Coaxial socket 2nd mating end all contact groupings

Precious Material And Location:

Contact surface gold and shell surface silver

Precious Material And Weight:

0.010 gold grains, troy and 0.100 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef and unef and unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0