NSN 5935-00-106-8264

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-106-8264

| Body | Style: |
|------|--------|
|------|--------|

Straight edge type w/mounting flange

Overall Length:

6.512 inches

Overall Height:

0.716 inches

Overall Width:

0.500 inches

Unthreaded Mounting Hole Diameter:

0.112 inches

Distance Between Mounting Facility Centers:

6.219 inches

Board Accommodated Length:

5.778 inches single board

Board Accommodated Width:

0.070 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bridged contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Connector Locking Method:

Spring friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

NSN 5935-00-106-8264

Electrical Receptacle Connector - Page 2 of 2



| Included Contact Quantity: |
|---|
| 36 single mating end single contact grouping |
| Included Contact Type: |
| Leaf spring single mating end single contact grouping |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-m-14 spec.