

View Online at <https://aerobasegroup.com/nsn/5935-00-107-4053>

Body Style:

Angle, shape, internal coupling

Overall Length:

1.205 inches

Overall Height:

0.880 inches

Overall Diameter:

0.450 inches

Environmental Protection:

Humidity resistant and vibration resistant

Cable Entrance Diameter:

Between 0.160 inches and 0.170 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

500.0 megahertz single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

140.0 and 280.0

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold and nickel

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact and shell surface gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0