NSN 5935-00-107-4242

Electrical Receptacle Connector - Page 1 of 2



| Electrical Neceptable Confidence 1 age 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/5935-00-107-4242 |
| Thread Class: |
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Height: |
| Between 2.859 inches and 2.891 inches |
| Overall Width: |
| Between 2.859 inches and 2.891 inches |
| Unthreaded Mounting Hole Diameter: |
| Between 0.164 inches and 0.174 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| Between 2.205 inches and 2.215 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| Between 2.205 inches and 2.215 inches |
| Distance From Mounting Shoulder To Front Face: |
| Between 0.484 inches and 0.516 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Lk110 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Polarization Method: |
| Key, multiple key groove |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| Thready Qty Per Inch (tpi): |
| 6 |
| Thread Size: |
| 2 500 inches |

Terminal Location:

Back single mating end single contact grouping

NSN 5935-00-107-4242

Electrical Receptacle Connector - Page 2 of 2



| Contact Material: |
|---|
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Insert Material: |
| Plastic melamine single mating end and plastic phenolic single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Included Contact Quantity: |
| 110 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold and contact surfaces silver |
| Precious Material And Weight: |
| 0.110 gold grains, troy and 0.110 silver grains, troy |
| Precious Material: |
| Gold and silver |
| Thread Series Designator: |
| Un |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Demilitarization:

No Fiig: A039b0