Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-108-7023

2a and 2b

**Thread Direction:** 

Right-hand

## Body Style:

Straight shape

## **Overall Length:**

1.630 inches

#### **Overall Height:**

0.570 inches

#### **Overall Width:**

0.390 inches

### **Distance Between Mounting Facility Centers:**

1.408 inches

#### **Threaded Device Type:**

Coupling facility and mounting stud

## Mating End Quantity:

1

### **Contact Position Arrangement Style:**

50 single mating end

## Contact Removability:

Nonremovable single mating end single contact grouping

## Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

#### **Polarization Method:**

Guide pin/socket

#### **Connector Locking Method:**

Jackscrew-socket

### Thread Size:

0.099 inches and 0.086 inches

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Insert Material:

Plastic diallyl phthalate single mating end

# **Terminal Type:**

Solder well single mating end single contact grouping

# Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end



**Included Contact Quantity:** 50 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.050 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc and unc Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-m-14 spec.